www.PapaCambridge.com

CAMBRIDGE INTERNATIONAL EXAMINATIONS

International General Certificate of Secondary Education

MARK SCHEME for the October/November 2013 series

0445 DESIGN AND TECHNOLOGY

0445/32 Paper 3 (Resistant Materials), maximum raw mark 50

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2013 series for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level components and some Ordinary Level components.

Page 2	Mark Scheme	Syllabus	. S. L.	
	IGCSE – October/November 2013	0445	100	

Section A

- 1 Lightweight, easy to cut/join/shape/work with/use. (2 × 1)
- 2 (a) coping saw, scroll saw, fret saw, Hegner or equivalent

[1]

(b) piercing saw, abra file saw

[1]

3 (a) spanner, wrench

[1]

(b) Allen key

[1]

4 (a) aluminium

[1]

(b) will not rust/corrode

[1]

- Brittle, liable to breaking off corners and/or edges, difficult to construct traditional joints, difficult to finish. (2 × 1)
- 6 Lightweight material, comfortable moulded shape, can be colourful, resistance to outdoors. (2 × 1)

[2]

7 Accuracy of completed joint (0–3) Award max. 2 marks if assembled

[3]

8 One wide board not practical, grain inverted for stability, boards/tree not wide enough, makes table top stronger. (2 × 1) [2]

9

Tool	Name Specific use		
	Pincers	Pulling out pins or nails	
28	Mortise gauge	Marking a pair of parallel lines, marking out a mortise and tenon joint	

								24	
	Page 3			Mark Scheme			Syllabus	S. 1	
				IGCSE –	October/Nov	vember 2013		0445	Par
10	Boa Dis	Vashing-up liquid bottle Soat hull Disposable cups Comb			polythene polyester resin, GRP polypropylene, polystyrene, Styrofoam, polythene polypropylene, nylon, ABS, acrylic				Papa Cambridge
					Se	ection B			`
11	(a)	try sq	uare.			encil, marking kn accuracy/quality c		ule, mortise and conmunication.	utting gauges,
				_		tenon saw, copi ccuracy/quality c	_	aw, chisel and mallonmunication.	et, files. [6]
	(b)	2 crai Corne Corne	mps only (1) er cramps: to er cramps: to) op & bot op or bo	· tom each corr ttom only (1)	·		n and 2 at 90°. (0–2	2)
		Sash cramps / corner cramps named (1)							
		Suital	ble adhesive	е. Ассер	t wide range o	of generic or trade	de nar	mes (1)	[5]
	(c)	ro A	oughly, file ι λccept hole :	up to ma saw: hole	rk. (4 × 1 stag	ies) named, fit in drill,		saw or equivalent,	cut out shape
		S	Sawing: keep Orilling: corre	p low in vect speed	vice, clamped d, drill angle, d	at must be linked in position, corre clamped securely loose clothing.	ect sa		[1]
	(d)				applied beads ipment used, a	/blocks. accuracy of infor	rmatio	n. (3 × 1)	[3]
	(e)	Pract Appro Mater	e form of hai ical idea (0- opriate shap rials (0–1) tructions an	-2) pe/sizes ((0–2)	es or jointed into t	top e	dge of 2 sides.	

[6]

Cut out handholds: Practical idea (0–2) Appropriate shape/sizes (0–2) Constructions and tools/equipment (0–2)

		32	_		
	Page 4		Mark Scheme	Syllabus	
			IGCSE – October/November 2013	0445	
12	(a) (b)	A scrib B [cen	ly cheap, plentiful, can be worked/joined in a variety ber, try square, marker pen, rule (1) htre/dot] punch, hammer (1) ders (1)	One	-
		C divid	iers (1)	[3]	1
	(c)	Held in v			
		Force rea	equired by hammer and scrap wood or mallet (1)	[3]	1
		1 0100 10	quired by Hammer and corap wood or mailer (1)	Įo.	
	(d)	cloth, flu	ion of method should include: preparation of meta ux joint, position on hearth with fire bricks, apply run, leave to cool (6 × 1)	•	.,
	(e)	drill tapp	ap and tap wrench to produce thread in stand: bing size hole, insert tap into tap wrench, start cut, a –3 dependent on technical accuracy, detail and qua		
		Position	lie and die stock to produce thread on arm: die on end of rod, appropriate technique. –3 dependent on technical accuracy, detail and qua	ality of communication. [6]
	(f)		orm of 'stop' or 'cap' shown clearly on end. t notes to support idea. (0–2)	[2]]
	(g)	Stand ca	an be more stable by means of increased width of n	netal, additional base.	
		Stability 1 Both dire Heavier I	I idea stability side to side (1) front to back (1) ections (2) base (2) t notes to support idea.	(0-2) (0-1) [3]]
13	(a)	•	I can be bent to shape easily, strength in all direc well (2 × 1)	ctions/ no grain weakness, can be	

(b) To check the appearance, check important sizes, prevents wasting resistant materials, can assist planning (2 × 1) [2]

Page 5			Mark Scheme	SvII	abus	0	
			IGCSE – October/November 2013		145	800	
(c)	Use of male and female formers shown clearly Cork or rubber sheet between plywood and formers Pressure applied by means of cramps Accuracy /quality of communication					(0- (0-1) (0-2)	Bridge
	bag	, with	vacuum forming bag award 4 × 1 for specifice hdraw air by /quality of communication	c stages: use	of former, a	dhesive, (0–4) (0–2)	seal (6)
(d)	(i)	Awa	e only joint that can work is a halving joint. ard max. 2 marks for uneven 'halves' ard 0–3 marks dependent upon accuracy/qual	ity of joint drav	vn		[3]
	(ii)		le variety of adhesives: generically, e.g. synth scamite, Aerolite, Resin 'W'	etic resin, PVA	A or trade na	ames suc	h as [1]
(e)	(i)	wipe	ges in preparation include: glasspaper and co e dust off with a damp cloth. ard 0–3 marks dependent upon the accuracy a			erent gra	des, [3]
	(ii)	Awa	table finish: wide range of varnishes, preserva ard 1 mark for appropriate named finish. ason includes: enhance appearance, protect, pard 1 mark for sensible reason.		clean.		[2]
(f)	Pra	ctical	l ideas: solid wood base, separate pieces atta	iched to provid	le stability		
	Methods of construction clearly shown/ appropriate					(0-2) (0-2) (2 × 1)	[6]