



DESIGN AND TECHNOLOGY

6043/01

Paper 1

October/November 2017

MARK SCHEME

Maximum Mark: 100

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge International will not enter into discussions about these mark schemes.

Cambridge International is publishing the mark schemes for the October/November 2017 series for most Cambridge IGCSE[®], Cambridge International A and AS Level components and some Cambridge O Level components.

© IGCSE is a registered trademark.

This document consists of **8** printed pages.

Part AAttempt all questions.

Question	Answer	Marks
1(a)	forstner bit, flat bit, drill, hole saw	1
1(b)	coping saw. Jigsaw, reciprocating saw	1
1(c)	dividers, compass	1
1(d)	centre punch, (masking tape)	1
1(e)	template	1
1(f)	marker pen, chinagraph pencil	1

Question	Answer	Marks
2(a)	bench hook	1
2(b)	holding work still to saw accurately	1

Question	Answer	Marks
3(a)	clear sketch of sash cramp	up to 2 2
3(b)	clear sketch of bradawl	up to 2 2

Question	Answer	Marks
4	beech does not splinter easily, takes a smooth finish, tough, takes knocks 1 × 2	2

Question	Answer	Marks
5	tempering – heat treatment process 1 to increase toughness 1 (reduces hardness)	2

Question	Answer	Marks
6(a)	Glass Reinforced Plastic (Polyester)	1
6(b)	vehicle body, kayak	1

Question	Answer	Marks
7	micrometer, Vernier calliper, (calliper and rule)	1 × 2
		2

Question	Answer	Marks
8	plastic cup – expanded polystyrene	1
	garden bench – teak, iroko, cedar, any other appropriate	1
	saucepan – aluminium alloy, stainless steel (copper)	1
		3

Question	Answer	Marks
9	tie hair back, wear goggles , secure work, any other appropriate	1 × 2
		2

Question	Answer	Marks
10	brass 1 copper 1 zinc 1 bronze 1 copper 1 tin 1 steel, 1 iron 1 carbon 1	
		3

Part B

Attempt four questions, two from Section 1 and two from Section 2.

Section 1 – Tools and Materials

Question	Answer	Marks
11(a)	Three tools identified and use stated A – Jack plane (accept smoothing or plane) – preparing flat surface on wood B – spokeshave – preparing curved shapes in wood C – rasp – shaping wood or foamed/expanded plastic 2 × 3	6
11(b)(i)	vertical adjustment by hand nut, lateral adjustment by lever, good description 2	6
11(b)(ii)	blade depth set by two adjusting screws 1 adjust each screw to ensure even depth 1	
11(b)(iii)	slicing, single cut action, good finish in A 1 – multiple ‘teeth’ cuts C , not as good a finish with C 1	
11(c)(i)	sketch of countersink bit – cutting csk for screw-heads up to 3	6
11(c)(ii)	sketch of tap wrench, purpose – turning tap to cut a thread up to 3	

Question	Answer			Marks
12	Material	Application	Properties	18
	Medium Density Fibreboard	Large furniture – wardrobes, table tops	Large surfaces available, smooth finish, dimensionally stable, Can be veneered, painted	
	Phenol formaldehyde	Electrical fittings, door handles, irons, saucepan handle	Heat resistant, usually dark products, stiff, hard material, can be used in laminates	
	Duralumin	Aircraft and vehicle parts	Ductile, malleable, corrosion resistant, lightweight	
	Acrylic	Shop signs, baths, rear light units on cars (school based projects)	Good optical qualities, variety of colours, better impact resistance than glass but scratches easily	
	Plywood	Thin ply used for laminated shapes, flooring, construction	Large surfaces available, cross grain effect very strong dimensionally stable, with water resistant adhesive can be used outdoors	
	Copper	Water pipes, electric cable, car radiators	Malleable, ductile, very good conductivity, heat and electrical	
1 for application, 2 for property/ function with link to application (1 × 6 + 2 × 6)				

Question	Answer			Marks
13(a)(i)	Hardwoods Ferrous Thermoplastic	Softwoods Non-ferrous thermosetting plastic	both for 1 both for 1 both for 1	3
13(a)(ii)	appropriate hardwood and softwood appropriate Ferrous and non-ferrous appropriate Thermoplastic and thermosetting plastic		2 2 2	6
13(b)	explanation should include: Material example e.g. specific hardwood , MDF, acrylic, specific metal 1, Hazard – dust inhalation , sharp edge , 1 Accept any other specific safety risks Precaution – masks, extractors, remove sharp edges, use gloves 1			3
13(c)(i)	explanation should include: product Availability, recyclability, obtaining/processing materials			1 up to 2

Question	Answer	Marks
13(c)(ii)	<p>explanation should include: product function, safety, appearance, market appeal</p> <p style="text-align: right;">1 up to 2</p>	3

Question	Answer	Marks
14(a)(i)	die (die holder)	1
14(a)(ii)	forstner bit, (flat bit, small point)	1
14(a)(iii)	coping saw, (abrafile), hegner saw	1
14(b)(i)	guillotine, shears/tinsnips, fine blade hack saw	12
14(b)(ii)	fine tooth saw, dovetail/tenon with guide, (fine blade coping saw with guide), band saw	
14(b)(iii)	<p>tenon saw with guide. Jigsaw, band saw</p> <p>Good communication 1, details of tools, holding work whilst cutting up to 3</p> <p style="text-align: right;">3 × 4</p>	
14(c)	<p>explanation could include: sharpness, quality finish, speed / ease of use, safety implications – up to 3</p>	3

Section 2 – Processes

Question	Answer	Marks
15(a)	Material could be – nylon, aluminium, brass, appropriate hardwood (birch/beech) Reasons could be, easy to turn, takes a good finish, aesthetically pleasing.	3 1 1 × 2
15(b)(i)	appropriate turning process including details of tools	up to 5
15(b)(ii)	appropriate application of quality control/measurement	up to 5
15(b)(iii)	appropriate method of achieving smooth finish	up to 5

Question	Answer	Marks
16	any two processes	18
16(a)	hollowing – cutting disc – tinsnips – annealing – – bossing mallet/hammer – leather sand bag – hammer – hollow wooden block, blocking hammer – final planishing/finish	most stages 9
16(b)	injection moulding – split mould prepared – plastic granules fall from hopper into heating chamber – archimedes screw injects into mould – remove and trim	most stages 9
16(c)	steam bending – prepare bending jig – steam strips in chamber until pliable – hold in bending jig – remove and trim to shape	most stages 9 2 × 9

Question	Answer	Marks
17(a)	suitable materials handle – aluminium, stainless steel, brass, (acrylic) nylon rod base – named hardwood, aluminium, copper acrylic, polystyrene	
17(a)(i)	processes could be – vacuum formed, pressed, turned Material 1 process 4	5
17(a)(ii)	processes could be – shaping using heat/jig Material 1 process 4	5
17(a)(iii)	joining process could be – riveting, , using threads, drilling and cementing Material 1 process 4	5
17(b)	appropriate modification	3

Question	Answer	Marks
18(a)(i)	mark out using sliding bevel, engineers blue engineers square, scriber Saw/file to shape Flux and braze Clean up most stages 6	12
18(a)(ii)	prepare former Cut veneer/thin ply to shape Glue and alternate grain Clamp up/vacuum bag Remove trim to shape/finish most stages 6	
18(a)(iii)	cut length of rectangular section nylon Mill (saw and file) shoulders File rounded shape Finish Or injection moulded Create two part mould Heat plastic granules, preheat mould Inject plastic Water cool mould Eject part/remove sprue most stages 6 Accept other appropriate processes 2 × 6	
18(b)	appropriate method of securely attaching the seat most stages 6	6